

TECHNICAL SHEET

STANDARD PERFORMANCE

1 JANUARY 2025



EXPO-LINE



Havenlaan 9,
3980 Tessenderlo
BE



2 Chemin De Montrichard
54700 Pont-à-Mousson
FR



www.expo-line.com



info@expo-line.com

TECHNICAL SHEET

STANDARD PERFORMANCE



DESCRIPTION

Standard Performance is the entry-level product within the Expo-Line Performance range.

It combines trusted Performance technology with a **very competitive price**, making it the ideal solution for clubs seeking both efficiency and quality.

- **No settling and no clumping** - always homogeneous and ready to use
- **Cost-effective choice** - excellent value for money
- **Versatile use** - suitable for training pitches, summer relining, and even main fields
- **Optimal dosage** - on average 5 to 7 L per pitch

With its excellent balance between price, consumption and quality, **Standard Performance** is the reliable choice for everyday use, and **particularly suitable for relining**.

GENERAL INFORMATION

Ready-to-use, biodegradable line paint with standard performance.

Packaging

11L cans

Dilution

Ready-to-use

Spraying equipment

Spray and air blast machines → Clean with water

Drying time

Approx. 5 to 10 minutes → Depending on weather conditions

Consumption

1 Football pitch = 7 to 11 litres / 1 rugby pitch = 14L

Storage

Frost-proof

TECHNICAL SHEET

STANDARD PERFORMANCE



PHYSICAL CHARACTERISTICS

AFNOR classification

PH : 8.8

Density : 1.09

Colour: Clear white

No sedimentation

Viscosity: 450 CPS

Titanium dioxide: 8%

Mineral filler: 7%

Resin: 0%

Dry extract : 14

The data in this data sheet have been compiled based on the latest laboratory data. Technical data are subject to modification or change. Users should ensure that they have access to the most recent data sheet. There is no representation that the project was complete. Since application, substrate quality and treatment conditions. No liability can be accepted on the basis of this data sheet